

Urea Solution 32.5% Industrial Grade

CHEMICAL ANALYSIS

Component	Units	Minimum	Maximum	Typical
Urea	wt. %	31.8	33.2	
Alkalinity as NH ₃	wt. %		0.2	
Biuret	wt. %		0.3	
Aldehydes	mg/kg		5	
Insoluble Matter	mg/kg		20	
Phosphate	mg/kg PO ₄		0.5	
Aluminum	mg/kg Al		0.5	
Calcium	mg/kg Ca		0.5	
Chromium	mg/kg Cr		0.2	
Copper	mg/kg Cu		0.2	
Iron	mg/kg Fe		0.5	
Magnesium	mg/kg Mg		0.5	
Nickel	mg/kg Ni		0.2	
Potassium	mg/kg K		0.5	
Sodium	mg/kg Na		0.5	
Zinc	mg/kg Zn		0.2	

PHYSICAL ANALYSIS

Component	Units	Minimum	Maximum	Typical
Density (68°F / 20°C)	lb/US gal			9.07 – 9.12
	kg/m ³			1087 - 1093
Refractive Index	@68°F / 20°C			1.381 - 1.384

Refer to a Safety Data Sheet for more information

Typical results are based on the analysis of a composite sample from a bulk shipment. Grab samples or individual car samples may fall outside of the typical range.

To the best of Nutrien's knowledge, the information contained herein is accurate and reliable as of the date compiled; however, Nutrien makes no representation, warranty or guarantee as to the information's accuracy, reliability, completeness or timeliness. It is the user's responsibility to determine the suitability and completeness of such information for the user's own uses or purposes. Nutrien does not accept any liability for any loss or damage that may occur from any use of this information.

Product is manufactured by the following subsidiary of Nutrien Ltd.:

Agrium US Inc. · 5296 Harvest Lake Drive · Loveland, CO · 80538 · (970) 685-3600 · 1-800-524-0132